

F-compression connector CX3 7.0 QM (Quick-mount) with o-ring, 50 pcs. box

Art. Number 360943



F-56-CX3 7.0 QM (Quick-mount)

F-compression connector quick mount for very easy mounting on the coax cables.

- Waterproof. With o-ring.
- Class A+
- Fast mounting, no braid fold back
- Perfect for hard cables with PE-jacket

Technical Specifications

ORDER INFORMATION

EAN Number 5702663609433

TRANSFER IMPEDANCE

Transfer Impedance @ 5-30 MHz | mΩ/m < 2.5 mΩ/m

CHARACTERISTICS

Cable type KOKA 110 A+,A++ & KOKA 550, KOKA 99, KOKA F6, KOKA 80

Tool 360920, 360919

FREQUENCY RANGE

Frequency range | MHz 0.3-3000 MHz

LOSS

Insertion loss (typ.) | dB 0.01 @ 860-1000 MHz dB

RETURN LOSS

Return Loss | dB > 34 @ 860-1000 MHz dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL



TRIAx

connecting the future

Technical Specifications

Screening Efficiency	EN50117 (Class A+)
Temperature - operating °C	-40...70 °C

MECHANICAL

Plating	NiTin 6
Colour	Blue
Packing QTY	100
Product Height mm	32 mm
Product Length mm	10 mm
Product Width mm	14 mm
Product Depth mm	14 mm
Packaging Height m	0.074 m
Packaging Width m	0.150 m
Packaging Depth m	0.058 m
Packaging Volume m3	0.000 m3
Net Weight kg	0.010 kg
Tara Weight kg	0.013 kg
Total Weight kg	0.023 kg